

CABOT PLASTICS

Product Information

PLASBLAK® XP6336A

BLACK POLYETHYLENE MASTERBATCH FOR FILM , SHEET EXTRUSION AND MOULDING APPLICATIONS

PLASBLAK® XP6336A is designed for general purpose film, sheet extrusion and moulding applications. PLASBLAK® XP6336A can also be used in compounding applications.

METHOD OF ADDITION

PLASBLAK® XP6336A is designed for ease of dilution and homogeneous mixing and is therefore suitable for direct addition using automatic dosing units or by pre-blending.

ADDITION RATE

The amount of masterbatch added depends on the performance requirements of the final application and the carbon black content specified in the finished product . Typical addition rates vary from 2% to 5% masterbatch (8% to 25% in mulch film).

PHYSICAL PROPERTIES

PROPERTY	VALUE	TEST METHOD (*)
Carrier	PE	
Pigment	50% carbon black	
Compatibility	LDPE, LLDPE, HDPE, PP, ethylene copolymers	
Density @ 23° C	1230 kg/m ³	CTM E023
MFI 10 kg/190° C	7 g/10 min	CTM E005 (ISO 1133)

(*) Tests are performed according to Cabot Test Methods (CTM) based on international Standards

Quoted test results should not be used for specification purposes but are typical test values intended for guidance only.

PACKAGING

PLASBLAK® XP6336A is supplied in regular pellet form packed in 25 kg bags. It should be stored in a dry place.

Recommended storage life: up to 1 year provided it is stored as directed.

This information is provided as a convenience and for informational purposes only . No guarantee or warranty as to this information, or any product to which it relates, is given or implied. This information may contain inaccuracies, errors or omissions and CABOT DISCLAIMS ALL WARRANTIES EXPRESS OR IMPLIED , INCLUDING MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AS TO (i) SUCH INFORMATION, (ii) ANY PRODUCT OR (iii) INTELLECTUAL PROPERTY INFRINGEMENT. In no event is Cabot responsible for, and Cabot does not accept and hereby disclaims liability for, any damages whatsoever in connection with the use of or reliance on this information or any product to which it relates .

Cabot Headquarters - EMEA
Durachpark
Mühlentalstrasse 36
Schaffhausen 8200
Switzerland
Tel: +41 (0)52 630 3838
Fax: +41 (0)52 630 3810

Cabot Brasil Industria e Comercio
Ltda.
Rua do Paraiso 148 - 5 andar
04103-000 Sao Paolo,
SP Brazil
Tel: +55 11 2144 6400
Tel: 0800 19 59 59 (Customer
service)
Fax: +55 11 3253 0051

Cabot China Ltd.
558 Shuangbai Road
Shanghai 201108
China
Tel: +86 21 5175 8800
Fax: +86 21 6434 5532

Cabot Customer Service Center
Interleuvenlaan 15 i
3001 Leuven
Belgium
Tel: +32 16 39 24 00
Fax: +32 16 39 24 44
Cabot Plastics Belgium S.A.
Research and Development Center
Rue Prevochamps 78
4860 Pepinster
Belgium
Tel: +32 87 39 27 11
Fax: +32 87 46 98 69
05

13

14

15

中国
卡博特（中国）投资有限公司
中国上海吴泾双柏路558号
邮编：201108
电话：+86 21 5175 8800
传真：+86 21 6434-5532

PLASBLAK®, PLASWITE®, PLASGREY®,
PLASADD®, CABELECO® and CABOT® are
registered trademarks of Cabot
Corporation
© Cabot Corporation, MA, U.S.A. All
rights reserved. 2012

GLOBAL CONNECTICS PLC.